



HEBEI RUNHE HYDRAULIC MACHINERY CO., LTD

Add: No.27 Zhonghua North Street, Xinhua District, Shijiazhuang City,
Hebei Province, China

Email: admin@hydraulicpumptechnology.com Tel/Whatsapp/Wechat: +8619932761114

G101/102 Hydraulic Motor



Product features:

- Pump-Valve Combination, Compact Structure, Light Weight, Widely Used In Dump Trucks, Garbage Trucks, Lifting Machinery, Etc.
- Built-In Reversing Valve, The Valve Can Be Manually Or Pneumatically Controlled, With Good Flow Control Capability
- Built-In Safety Valve To Protect The Cylinder And System From Overload
- The System Intermittent Load Adopts a 2-Circuit Design, And The System Intermittent Or Continuous Load Adopts a 3-Circuit Design
- G101 Has Two Shaft Extensions, Which Can Be Connected To The Power Output Shaft For Forward And Reverse Rotation Respectively

G101/102 Gear Pump Performance Parameters

Displacement (mL/rev)	Tooth width (in)	Rated pressure (MPa)	Maximum pressure (MPa)	Rated speed (RPM)	Maximum speed (RPM)	Rated operating output flow rate (LPM)	Input Power (KW)
24.2	3/4 "	13.8	17.2	1800	2400	36	11.6
48.5	1 1/2 "	13.8	17.2	1800	2400	79	23.5
64.6	2 "	13.8	17.2	1800	2400	110	31